

Page 1/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.07.2020 Version number 4 Revision: 28.07.2020

SECTION 1: Identification of the substance/mixture and of the company/ undertakina

- · 1.1 Product identifier
 - · Trade name: Paladon 65 liquid
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
 - · Application of the substance / the mixture Manufacture of dental prothesis
- · 1.3 Details of the supplier of the safety data sheet
 - Manufacturer/Supplier:

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

Tel.: +49 (0)800 4372522

- · Informing department: E-Mail: msds@kulzer-dental.com
- · 1.4 Emergency telephone number: Emergency CONTACT (24-Hour-Number): +49 (0)6132-84463

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
 - Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

methyl methacrylate

tetramethylene dimethacrylate

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smokina.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

· 2.3 Other hazards -

Results of PBT and vPvB assessment

· PBT: Not applicable.

(Contd. on page 2)



Page 2/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.07.2020 Version number 4 Revision: 28.07.2020

Trade name: Paladon 65 liquid

· vPvB: Not applicable.

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
 - · Description: Product based on methacrylates

· Dangerous components:		
CAS: 80-62-6	methyl methacrylate	>90%
EINECS: 201-297-1 Reg.nr.: 01-2119452498-28-XXXX	Flam. Lig. 2, H225 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 2082-81-7	tetramethylene dimethacrylate	<i>≥1-≤</i> 5%
EINECS: 218-218-1 Reg.nr.: 02-2119849716-25	Skin Sens. 1B, H317	
CAS: 99-85-4	p-Mentha-1,4-diene	<0.25%
EINECS: 202-794-6	Flam. Liq. 3, H226 Repr. 2, H361 Aquatic Chronic 2, H411	

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
 - After inhalation Supply fresh air; consult doctor in case of symptoms.
 - After skin contact instantly wash with water and soap and rinse thoroughly.
 - After eye contact Rinse opened eye for several minutes under running water.
 - After swallowing

Rinse out mouth and then drink plenty of water.

In case of persistent symptoms consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
 - **Suitable extinguishing agents** CO2, sand, extinguishing powder. Do not use water. **For safety reasons unsuitable extinguishing agents** Water.
- · 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
 - Protective equipment: No special measures required.
 - Additional information -

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Prevent material from reaching sewage system, holes and cellars. (Contd. on page 3)



Page 3/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.07.2020 Version number 4 Revision: 28.07.2020

Trade name: Paladon 65 liquid

(Contd. of page 2)

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues). Do not flush with water or aqueous cleansing agents

Send for recovery or disposal in suitable containers.

6.4 Reference to other sections

See Section 13 for information on disposal.

See Section 8 for information on personal protection equipment.

_

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
 - Storage
 - · Requirements to be met by storerooms and containers: Store in cool location.
 - Information about storage in one common storage facility: Not required.
 - Further information about storage conditions:

Store cool (not above 25 °C).

Store in cool, dry conditions in well sealed containers.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

80-62-6 methyl methacrylate

OES () Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm

DNELs

80-62-6 methyl methacrylate

Dermal worker industr., I.te., syst. 74.3 mg/Kg/d (human) Inhalative worker industr., I.te., syst. 210 mg/m3 (human)

PNECs

80-62-6 methyl methacrylate

freshwater 0.94 mg/l (aqua)

· Additional information: The lists that were valid during the compilation were used as basis.

- · 8.2 Exposure controls
 - Personal protective equipment
 - General protective and hygienic measures

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

(Contd. on page 4)



Page 4/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.07.2020 Version number 4 Revision: 28.07.2020

Trade name: Paladon 65 liquid

(Contd. of page 3)

Breathing equipment:

Not neccessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

If skin contact cannot be avoided, protective gloves are recommended to avoid possible sensitization.

Solvent resistant gloves

Check protective gloves prior to each use for their proper condition.

recommended

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR Nitrile rubber, NBR

- Eye protection: Tightly sealed safety glasses.
- · Body protection: Light weight protective clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and of General Information Appearance:	chemical properties
· Form: · Colour: · Smell:	Fluid Colourless Ester-like
· Odour threshold:	Not determined.
· pH-value:	Not determined.
Change in condition Melting point/freezing point: Initial boiling point and boiling ra	-48 °C ange: 101 °C
· Flash point:	10 °C
· Inflammability (solid, gaseous)	Not applicable.
· Ignition temperature:	430 °C
· Decomposition temperature:	Not determined.
· Self-inflammability:	Product is not selfigniting.
	Product is not explosive. However, formation of

(Contd. on page 5)



Page 5/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.07.2020 Version number 4 Revision: 28.07.2020

Trade name: Paladon 65 liquid

		(Contd. of page 4
Critical values for explosion: Lower: Upper:	2.1 Vol % 12.5 Vol %	
· Steam pressure at 20 °C:	47 hPa	
Density at 20 °C Relative density Vapour density Evaporation rate	0.940 g/cm³ Not determined. Not determined. Not determined.	
Solubility in / Miscibility with Water:	Not miscible or difficult to mix	
· Partition coefficient: n-octanol/wa	ater: Not determined.	

1 mPas

· Viscosity:

· dynamic at 20 °C:

kinematic: Not determined.

• **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
 - · Conditions to be avoided: No decomposition if used and stored according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None
 - · Additional information:

If stored longer than recommended and/or above recommended temperature, product may polymerize generating heat.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
 - · Acute toxicity Based on available data, the classification criteria are not met.

· LD/	· LD/LC50 values that are relevant for classification:				
80-62-6 m	80-62-6 methyl methacrylate				
Oral	LD50	~7,900 mg/kg (rat)			
Dermal	LD50	>5,000 mg/kg (rab) (OECD 402)			
Inhalative	LC50/4 h	29.8 mg/l (rat)			
2082-81-7	2082-81-7 tetramethylene dimethacrylate				
Oral	LD50	10,066 mg/kg (rat) (OECD 401)			
99-85-4 p-	99-85-4 p-Mentha-1,4-diene				
Oral	LD50	>2,000 mg/kg (rat) (OECD 423)			
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)			

· Primary irritant effect:

• **Skin corrosion/irritation**• Causes skin irritation.

(Contd. on page 6)



Page 6/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.07.2020 Version number 4 Revision: 28.07.2020

Trade name: Paladon 65 liquid

(Contd. of page 5)

· Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
 - · Germ cell mutagenicity Based on available data, the classification criteria are not met.
 - · Carcinogenicity Based on available data, the classification criteria are not met.
 - · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
 - · Aquatic toxicity:

80-62-6 methyl methacrylate

EC50/48h 69 mg/l (daphnia)

LC50/96h 191 mg/l (fish)

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
 - · Additional ecological information:
 - · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

- · 12.5 Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
 - · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

European waste catalogue

18 01 06* | chemicals consisting of or containing hazardous substances

- Uncleaned packagings:
 - · Recommendation:

Disposal must be made according to official regulations.

Non contaminated packagings can be used for recycling.

CP

(Contd. on page 7)



Page 7/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.07.2020 Version number 4 Revision: 28.07.2020

Trade name: Paladon 65 liquid

(Contd. of page 6)

44 4 LIN Normalian	
14.1 UN-Number · ADR, IMDG, IATA	1247
14.2 UN proper shipping name	
· ADR	1247 METHYL METHACRYLA
	MONOMER, STABILIZED, solution
· IMDG, IATA	METHYL METHACRYLATE MONOME STABILIZED, solution
14.3 Transport hazard class(es)	OTABILIZED, GOIGION
· ADR	
ADA	
3	
	0.754) 51
· Class · Label	3 (F1) Flammable liquids.
· IMDG, IATA	
MIDO, IATA	
s	
	0.51
· Class · Label	3 Flammable liquids. 3
14.4 Packing group	•
· ADR, IMDG, IATA	II .
14.5 Environmental hazards:	
· Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
· Kemler Number: · EMS Number:	339 F-E,S-D
	·
14.7 Transport in bulk according to Annex Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	-
UN "Model Regulation":	UN1247, METHYL METHACRYLA
o moder togatation i	MONOMER, STABILIZED, solution, 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 - · Directive 2012/18/EU

 - Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 8)



Page 8/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.07.2020 Version number 4 Revision: 28.07.2020

Trade name: Paladon 65 liquid

(Contd. of page 7)

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H361 Suspected of damaging fertility or the unborn child.

H411 Toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 * Data compared to the previous version altered.

GB